Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Led	isons
------------------------------------	-------

Supplier's address: Ledisons, Rendementstraat 5, 8094RA Hattemerbroek, NL

Model identifier: LDF71-272-27N

T	- 6	10 - 1- 1		
IVna	α T	IIσnt	source:	,
IVDC	vı	HEILL	Jourte.	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
Product parameters			

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
Energy consummode (kWh/10 up to the neares	00 h), rounded	3	Energy efficiency class	E
a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	250 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P _{on}), ex-	2,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-
	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	76	Spectral power dis-	See image
sions without	Width	45	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	45	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if			
any (millime- tre)			
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	25
		Chromaticity coordi-	0,458
		nates (x and y)	0,410
Parameters for LED and OLED	light sources:		
R9 colour rendering index valu	ie 1	Survival factor	0,90
the lumen maintenance factor	0,93		
Parameters for LED and OLED	mains light sources:		
displacement factor (cos φ1)	0,00	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated balast of a particular wattage.	nt	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

